



March 9, 2017

Jörn Stöver, Export Sales Manager, Overseas  
SATA GmbH & Co. KG  
Domertalstraße 20  
70806 Kornwestheim, Germany

RE: Approval of SATAminijet 4400 B RP Spray Guns for Butte County

The Butte County Air Quality Management District (District) has completed our review of your request regarding the SATAminijet 4400 B RP Spray Guns use in Butte County. Per South Coast AQMD letter, the results of the transfer efficiency testing indicate that the SATAminijet 4400 B RP Spray Guns are capable of achieving equivalent or better transfer efficiency than high-volume, low-pressure spray equipment. The District approves SATAminijet 4400 B RP Spray Guns for operations subject to Rule 235—*Requirements for Vehicle and Mobile Equipment*, under Section 3.5.5. This approval is subject to the following conditions:

1. A written notification will accompany each SATAminijet 4400 B RP Compliant Spray Gun sold or distributed for use with the District that states the spray gun is only approved for application of coatings subject to District Rule 235.
2. The maximum allowed pressure to the Compliant Spray gun shall not exceed 35 psig. A clearly visible, permanent label specifying the maximum inlet pressure shall be attached to each spray gun for sale or distribution within the District.
3. Each SATAminijet 4400 B RP Spray Gun sold or distributed within the District shall include a SATA air micrometer with gauge 0/845 (product number 27771), SATA adam 2 digital air micrometer with gauge (product number 130278), or SATA adam 2 U digital air micrometer with gauge (product number 195222) and shall include written notification attached to the spray gun that the use of this part in good working condition is required during actual operation.
4. This authorization is only valid if the SATAminijet 4400 B RP Spray Gun has the above required labels and gauges during actual operation.
5. Any modification to the spray gun design invalidates this approval unless such modification is approved by the District.

The District has attached an invoice for the minimum 1 hour evaluation time to review and approve your request. If you have any questions regarding this approval, please contact me at (530) 332-9400, extension 107 or via email at [d Lus k@bcaqmd.org](mailto:d Lus k@bcaqmd.org).

Sincerely,

A handwritten signature in blue ink that reads "David J. Lusk". The signature is fluid and cursive.

David J. Lusk  
Senior Air Quality Engineer

Enclosures: District Rule 235  
Invoice



## RULE 235

## 1 DEFINITIONS

- 1.1 **Active Solvent Losses:** The active solvent losses are the emissions during all steps of a spray gun equipment cleaning operation and are expressed in units of grams of solvent loss per cleaning cycle.
- 1.2 **Antiglare/Safety Coating:** A coating which does not reflect light.
- 1.3 **Camouflage Coating:** A coating applied on motor vehicles to conceal such vehicles from detection.
- 1.4 **Catalyst:** A substance whose presence initiates the reaction between chemical compounds.
- 1.5 **Color Match:** The ability of a repair coating to blend into an existing coating so that color difference is not visible.
- 1.6 **Coating:** A liquid, liquefiable or mastic composition which is converted to a solid protective, decorative or functional adherent film after application as a thin layer.
- 1.7 **Electrophoretic Dip:** A coating application method where the coating is applied by dipping the component into a coating bath and an electrical potential difference exists between the component and the bath.
- 1.8 **Electrostatic Application:** A sufficient charging of atomized paint droplets to cause deposition principally by electrostatic attraction. This application shall be operated at a minimum of 60 KV power.
- 1.9 **Extreme Performance Coating:** Any coating used on the surface of a vehicle, mobile equipment or their parts or components which is exposed to extreme environmental conditions such as high temperatures, corrosive or erosional environments, during the vehicle's principal use.
- 1.10 **Four-Stage Coating System:** A topcoat system composed of a ground coat portion, a pigmented basecoat portion, a semi-transparent midcoat portion, and two transparent clearcoat portions. Four-stage coating systems' VOC content shall be calculated according to the following formula:

$$\text{VOC T4-stage} = \frac{\text{VOC}_{gc} + \text{VOC}_{bc} + \text{VOC}_{mc} + 2 \text{VOC}_{cc}}{5}$$

Where:

VOC T4-stage = the average of the VOC content as applied in the ground coat (gc), basecoat (bc), midcoat (mc) and clearcoat (cc) system.

- VOC<sub>gc</sub> = the VOC content as applied of any given groundcoat  
 VOC<sub>bc</sub> = the VOC content as applied in the basecoat  
 VOC<sub>mc</sub> = the VOC content as applied of any given midcoat  
 2VOC<sub>cc</sub> = two times the VOC content as applied of any given clearcoat

**1.11 Grams of VOC Per Liter of Coating Less Water And Less Exempt Organic Compounds:** The weight of VOC per combined volume of VOC and coating solids and can be calculated by the following equation:

$$\text{Grams of VOC per Liter of Coating Less Water and Less Exempt Organic Compounds} = \frac{W_s - W_w - W_{es}}{V_m - V_w - V_{es}}$$

Where:

- W<sub>s</sub> = Weight of volatile compounds (grams)  
 W<sub>w</sub> = Weight of water (grams)  
 W<sub>es</sub> = Weight of exempt organic compounds (grams)  
 V<sub>m</sub> = Volume of material (liters)  
 V<sub>w</sub> = Volume of water (liters)  
 V<sub>es</sub> = Volume of exempt organic compounds (liters)

**1.12 Grams of VOC Per Liter of Material:** The weight of VOC per volume of material and can be calculated by the following equation:

$$\text{Grams of VOC per Liter of Material} = \frac{W_s - W_w - W_{es}}{V_m}$$

Where:

- W<sub>s</sub> = Weight of volatile compounda (grams)  
 W<sub>w</sub> = Weight of water (grams)  
 W<sub>es</sub> = Weight of exempt organic compounds (grams)  
 V<sub>m</sub> = Volume of material (liters)

**1.13 Group I Vehicles:** These vehicles include passenger cars, large/heavy duty truck cabs and chassis, light and medium duty trucks and vans, and motorcycles.

**1.14 Group II Vehicles:** These vehicles include public transit buses.

**1.15 Gun Washer:** Electrically or pneumatically operated system that is designed to clean spray application equipment while enclosed. A gun washer may also be a gun cleaning system that consists of spraying solvent into an enclosed container using a snug fitting.

**1.16 Hand Application Methods:** The application of coating by nonmechanical hand-held equipment including but not limited to paint brushes, hand rollers, caulking guns, trowels, spatulas, syringe daubers, rags and sponges.

- 1.17 **High-Volume, Low-Pressure Application (HVLP):** Spray equipment which uses a high volume of air delivered at pressures between 0.1 and 10 pssig.
- 1.18 **Low Emission Spray Gun Cleaner:** Any properly used spray equipment cleanup device which has passive solvent losses of no more than 0.6 grams per hour and has active solvent losses of no more than 15 grams per operating cycle as defined by the test method in Section 5.6 of this Rule.
- 1.19 **Metallic/Iridescent Topcoat:** Any topcoat which contains more than 5 g/l (.042 lb/gal) of iridescent particles, composed of metal as metallic particles or silicon as mica particles, as applied, where such particles are visible in the dried film.
- 1.20 **Mobile Equipment:** Any equipment, other than vehicles (as defined in this Rule), which may be drawn or is capable of being drawn on a roadway, including, but not limited to, truck trailers, camper shells, mobile cranes, bulldozers, concrete mixers, street cleaners, golf carts, all terrain vehicles, implements of husbandry, and hauling equipment used inside and around airports, docks, depots and industrial and commercial plants, but excluding utility bodies.
- 1.21 **Operating Cycle:** An operating cycle consists of all steps carried out during a cleaning operation.
- 1.22 **Passive Solvent Losses:** The passive solvent losses are the emissions from spray gun cleaning equipment when the equipment sits idle between cleaning cycles and are a result of natural evaporation from the equipment.
- 1.23 **Prep Station:** Any spraying area that meets the requirements for a "Limited Spraying Area" from Section 45.207 of the Uniform Fire Code and that prevents the escape to the atmosphere of overspray particulate matter using properly maintained filters and positive mechanical ventilation.
- 1.24 **Pretreatment Wash Primer:** Any coating which contains a minimum of 0.5% acid by weight which is necessary to provide surface etching and is applied directly to bare metal surfaces to provide corrosion resistance and adhesion.
- 1.25 **Primer:** Any coating applied prior to the application of a topcoat for the purpose of corrosion resistance and adhesion of the topcoat.
- 1.26 **Primer Sealer:** Any coating applied prior to the application of a topcoat for the purpose of corrosion resistance, adhesion of the topcoat, color uniformity, and to promote the ability of an undercoat to resist penetration by the topcoat.

- 1.27 Primer Surfacer:** Any coating applied prior to the application of a topcoat for the purpose of corrosion resistance, adhesion of the topcoat, and which promotes a uniform surface by filling in surface imperfections.
- 1.28 Reactive Organic Compound (ROC):** For the purpose of this Rule, the term "reactive organic compounds" (ROCs) are assumed to be the same as these compounds defined under the "volatile organic compound" (VOC) definition. (See VOC definition).
- 1.29 Reducer:** Any volatile liquid used to reduce the viscosity of the coating. This liquid may be solvents, diluents or mixtures of both.
- 1.30 Specialty Coatings:** Coatings which are necessary due to unusual and uncommon job performance requirements. These coatings include, but are not limited to, weld-thru primers, adhesion promoters, uniform finish blenders, elastomeric materials, gloss flatteners, bright metal trim repair and antiglare/safety coatings.
- 1.31 Spray Booth:** Any power ventilated structure of varying dimensions and construction provided to enclose or accommodate a spraying operation and which meets the Uniform Fire Code. A spray booth shall confine and limit, by dry or wet filtration, the escape to the atmosphere of overspray particulate matter.
- 1.32 Three-Stage Coating System:** A topcoat system composed of a pigmented basecoat portion, a semi-transparent midcoat portion, and two transparent clearcoat portions. Three-stage coating systems' VOC content shall be calculated according to the following formula:
- $$\text{VOC T3-stage} = \frac{\text{VOC}_{bc} + \text{VOC}_{mc} + 2 \text{VOC}_{cc}}{4}$$
- Where:
- VOC T3-stage = the average of the VOC content as applied in the basecoat (bc), midcoat (mc) and clearcoat (cc) system
- VOC<sub>bc</sub> = the VOC content as applied in the basecoat
- VOC<sub>mc</sub> = the VOC content as applied of any given midcoat
- 2VOC<sub>cc</sub> = two times the VOC content as applied of any given clearcoat
- 1.33 Topcoat:** Any coating applied over a primer or an original OEM finish for the purpose of protection or appearance.
- 1.34 Transfer Efficiency:** The ratio of the weight of coating solids which adhere to the object being coated to the weight amount of coating solids used in the application process, expressed as a percentage.

- 1.35 Two-Stage Coating System:** A topcoat consisting of a pigmented basecoat and a transparent clearcoat. Two-stage coating systems' VOC content shall be calculated according to the following formula:

$$\text{VOC T2-stage} = \frac{\text{VOC}_{bc} + 2\text{VOC}_{cc}}{3}$$

Where:

VOC T2-stage = the average of the VOC content as applied in the basecoat (bc) and clearcoat (cc) system

VOC<sub>bc</sub> = the VOC content as applied in the basecoat

VOC<sub>cc</sub> = the VOC content as applied of any given clearcoat

- 1.36 Undercoat:** Any pretreatment wash primer, precoat, primer, primer surfacer or primer sealer.
- 1.37 Utility Body:** A special purpose compartment or unit that will be bolted, welded or affixed onto an existing cab and chassis. The compartment may serve as storage for equipment or parts.
- 1.38 Vehicle:** A vehicle is any of the following: passenger cars, large/heavy duty truck cabs and chassis, light and medium duty trucks and vans, motorcycles, public transit busses, or military tanks or other tracked military vehicles.
- 1.39 Volatile Organic Compounds (VOC):** Any compound containing at least one atom of carbon, excluding any **Exempt Compound** as identified in Rule 102 Definitions. (For the purposes of implementing Butte County Air Quality Management District (DISTRICT) Rule 430 *New Source Review* and Rule 431 *Emission Reduction Credits And Banking*, the term VOC is assumed to be the same as those compounds defined under the VOC definition.)
- 1.40 Water-Based Temporary Transit Coating:** Any water-based coating that is intended to protect new motor finishes from certain forms of damage such as iron dust, soot, acid rain, and other airborne pollutants during transit and is removed prior to sale of the vehicle.
- 1.41 Weld-Thru Primer:** Any primer applied from an aerosol can, 16 ounces or less, to bare steel prior to welding that steel area. The purpose of the weld-thru primer is to inhibit corrosion in the weld area.

## 2 APPLICABILITY.

- 2.1 General Application:** The provisions of this Rule apply to any person who supplies, sells, offers for sale, applies or specifies the use of coatings for vehicles, mobile equipment and their parts or components.

**2.2 Effective Date:** The provisions of this Rule shall become effective January 1, 1998.

**3 REQUIREMENTS.**

**3.1 Coating VOC Content:** After the date expressed below, no person shall manufacture, solicit, require for use, specify, sell, or coat any vehicle, mobile equipment, or their parts or equipment, as defined in this Rule, using any coating with a Volatile Organic Compound (VOC) content in excess of the following limits, expressed as grams of VOC per liter of coating applied (lbs/gal), excluding water and exempt organic compounds, except as provided pursuant to Section 3.4 "Add-on Control Equipment Option", or Section 4 "Exemptions" of this Rule:

**Limits**

Grams of VOC per Liter of Coating (lbs/gal), Less Water and Less Exempt Organic Compounds:

	<i>January 1, 1998</i>		<i>July 1, 1999</i>	
	Group I Vehicles & Color Match for Group II Or Mobile Equipment	Group II Vehicles Or Mobile Equipment No Color Match	Group I Vehicles & Color Match for Group II Or Mobile Equipment	Group II Vehicles Or Mobile Equipment No Color Match
Pretreatment Wash Primer	780 (6.5)	780 (6.5)	780 (6.5)	780 (6.5)
Primer/Primer Surfacer	575 (4.8)	575 (4.8)	340 (2.8)	340 (2.8)
Primer Sealer	550 (4.6)	550 (4.6)	420 (3.5)	340 (2.8)
Single-Stage/Two-Stage Topcoats	600 (5.0)	420 (3.5)	600 (5.0)	420 (3.5)
Topcoats of More Than Two Stages	625 (5.2)	420 (3.5)	600 (5.0)	420 (3.5)
Specialty Coating	840 (7.0)	840 (7.0)	840 (7.0)	840 (7.0)
Extreme Performance	-----	750 (6.2)	-----	750 (6.2)
Camouflage	-----	420 (3.5)	-----	420 (3.5)

**3.2 Coatings Containing 1,1,1-Trichloroethane:** No person shall apply any coating to any vehicle, mobile equipment, or their parts or components, if that coating contains 1,1,1-trichloroethane.

**3.3 Extreme Performance Coating Petition:** Any person seeking to apply an extreme performance coating as defined in this Rule to a vehicle, mobile equipment, or their parts or components shall comply with the following requirements:

**3.3.1** A petition shall be submitted to the Air Pollution Control Officer



- (APCO) stating the performance requirements, volume of coating and VOC level that is attainable.
- 3.3.2** If the APCO grants written approval, then that approval shall be valid for one year. If applicable, such petition shall be resubmitted on an annual basis.
- 3.3.3** If the APCO grants written approval, such approval shall contain volume and VOC limit conditions.
- 3.4 Add-On Control Equipment Option:**
- 3.4.1** A person may comply with the provisions of Section 3.1 above, "Coating VOC Content" limits, by using air pollution control equipment provided that:
- 3.4.1.1** The combined control and capture efficiency shall reduce VOC emissions from an emission device by at least 85 percent, by weight; and,
- 3.4.1.2** The control system must be designed and operated for the maximum collection of fugitive emissions according to the U.S. EPA's "Guideline for Developing Capture Efficiency Protocols; and,
- 3.4.1.3** Written approval in the form of an Authority to Construct and a Permit to Operate for such equipment is received from the APCO.
- 3.4.2** A person may comply with the provisions of Section 3.5 below, "Transfer Efficiency" by using add-on control equipment provided the combined control and capture efficiency of VOC is at least 92 percent, by weight.
- 3.5 Transfer Efficiency:** No person shall apply any coating to any vehicle or mobile equipment or their parts and components unless one of the following methods is properly used:
- 3.5.1** Hand application methods
- 3.5.2** Electrophoretic dip coatings
- 3.5.3** Electrostatic application
- 3.5.4** High-Volume, Low-Pressure (HVLP) application
- 3.5.5** Any other coating application method which has been demonstrated to be capable of achieving at least 65 percent transfer efficiency.
- 3.6 Compliance Statement Requirement:** The manufacturer of coatings subject to this Rule shall include a designation of the VOC content as supplied, including coating components, expressed in grams per liter (g/l) or pounds per gallon (lbs/gal), excluding water and exempt organic compounds, on labels or data sheets. This designation shall include a statement of the manufacturer's recommendation regarding thinning, reducing, or mixing with any other VOC containing materials. This statement shall include the VOC on an as-applied basis, excluding water and exempt organic compounds, based on the manufacturer's recommendations.

- 3.7 Surface Preparation And Cleanup Solvent:** The requirements of this Subsection shall apply to any person using organic solvent for surface preparation and cleanup.
- 3.7.1** Closed containers shall be used for the storage or disposal of solvent-containing cloth or paper used for surface preparation and cleanup. Containers shall be nonabsorbent.
- 3.7.2** No person shall use organic compounds for spray equipment cleanup unless an enclosed gun washer or "low emission spray gun cleaner" as required by this Rule is properly used for cleaning.
- 3.7.3** No person shall use VOC-containing materials which have a VOC content of more than 200 g/l (1.67 lbs/gal) of material for substrate surface preparation prior to coating. This limit shall not apply to surface preparation material applied from a hand-held spray container. The VOC limit for VOC-containing material applied from hand-held spray containers shall not exceed 780 g/l (6.5 lbs/gal).
- 3.8 Storage Of VOC-Containing Materials:** All VOC containing materials, including but not limited to, fresh or spent solvent, coatings and reducers, shall be kept in closed containers when not in use.
- 3.9 Spray Booths And Prep Stations:** Effective January 1, 1998, no person shall apply any coating to any complete (entire) vehicle unless that application is performed within a properly maintained and operated Spray Booth. All spraying of parts or components of a vehicle shall be done in a properly maintained and operated Prep Station or Spray Booth.

#### 4 EXEMPTIONS.

- 4.1 Coatings In A Nonaerosol Container:** The "Coating VOC Content" limit sales prohibition in Section 3.1, and "Transfer Efficiencies" in Section 3.5 above shall not apply to the sale of any coating supplied in a nonaerosol container with a capacity of 16 fluid ounces or less, and shall not apply to any coating supplied in a handheld, nonrefillable aerosol container.
- 4.2 Approved VOC Add-On Controls:** The "Coating VOC Content" limit sales prohibition in Section 3.1 above shall not apply to the sale of coatings where the emissions to the atmosphere from the application of those coatings are controlled by a DISTRICT approved VOC add-on control device that meets the requirements of Section 3.4 above "Add-On Control Equipment Option".
- 4.3 Coatings Shipped Outside The District:** The sales prohibition in Section 3.1 above "Coating VOC Content" limit, shall not apply to any coating shipped outside of the District for use outside the District, or sold in the District for use outside the District.

- 4.4 Logos, Letters, Numbers And Graphics:** Any application of logos, letters, numbers and graphics to a painted surface, with or without a template, shall be exempt from this Rule.
- 4.5 Residential Dwellings:** Any coating operation of a vehicle by a resident of a one or two-family dwelling shall be exempt from this Rule provided:
- 4.5.1** The resident is the registered owner of the vehicle being coated;
  - 4.5.2** The coating operation is not being conducted as a business;
  - 4.5.3** The coating operation is limited to two vehicles per year;
  - 4.5.4** The coating operation does not cause a public nuisance.
- 4.6 Shape And Size Exemption:** With prior written approval of the APCO and on a limited term basis, the requirements of Section 3.9 above "Spray Booths And Prep Stations," shall not apply to the coating of vehicle(s) which due to shape or size, cannot reasonably be contained in any available substitute spray booth.
- 4.7 Spray Booths And Prep Stations Exemption:** The requirements of Section 3.9 above "Spray Booths And Prep Stations," shall not apply to:
- 4.7.1** Any repair, touch-up or spot priming operation which does not exceed a total of nine (9) square feet per vehicle. All operations shall be conducted in a controlled area such that a public nuisance is not caused to surrounding receptors.
  - 4.7.2** Any weld-thru primer.
  - 4.7.3** Any application of coatings to owner-operated agricultural vehicles.
  - 4.7.4** Any application of coatings to owner-operated construction vehicles.

## 5 TEST METHODS.

- 5.1 VOC Content:** Coating VOC content shall be determined using U.S. EPA Method 24. The exempt organic compound content of coatings or solvents shall be determined using ASTM Method D4457-85. Compliance with the prohibition of sale shall be determined by measuring the VOC content of each and every component of a coating or coating system which has been reduced using the manufacturer's recommended type and maximum amount of reducer.
- 5.2 Acid Content:** The measurement of acid content or pretreatment wash primers shall be done in accordance with ASTM Method D1613-85 (modified).
- 5.3 Metal And Silicon Content:** The measurement of the metal and silicon content of metallic/iridescent coatings shall be determined by the South Coast Air Quality Management District Method No. 318, "Determination of Weight Percent of Elemental Metal in Coatings by X-Ray Diffraction."

**5.4 Collection Efficiency And Capture Efficiency:** The collection and capture efficiency of organic emissions as specified in Section 3.5 of this Rule, shall be measured as follows:

**5.4.1** Capture efficiency shall be determined by the U.S. EPA Guidelines for Developing Capture Efficiency Protocols from the Federal Register Part 55 FR 26865, June 29, 1990.

**5.4.2** Measurement of vapor flow through pipes shall be determined by U.S. EPA Method 2A.

**5.4.3** Measurement of organic vapor concentration shall be determined by U.S. EPA Method 25A. The calculation of control device efficiency shall be determined only during periods of continuous coating operation not to exceed 24 hours.

**5.5 Transfer Efficiency:** Transfer Efficiency shall be determined using a method which shall be modeled after the test method described in the U.S. EPA document (EPA/600/2-88/-26b) "Development of Proposed Standard Test Method for Spray Painting Transfer Efficiency."

**5.6 Active And Passive Solvent Losses:** The active and passive solvent losses from spray gun cleaning systems shall be determined using South Coast AQMD "General Test Method for Determining Solvent Losses from Spray Gun Cleaning Systems" dated October 3, 1989. The test solvent for this determination shall be any lacquer thinner with a minimum vapor pressure of 105 mm Hg at 20°C. The minimum test temperature shall be 15°C.

## 6 MONITORING AND RECORDKEEPING REQUIREMENTS.

**6.1 General Monitoring And Recordkeeping Requirements:** Any person subject to this Rule shall:

**6.1.1** Maintain and make available to DISTRICT personnel, a current list of coatings (including specialty coatings) and solvents in use that provides all of the data necessary to evaluate compliance, including the following information, as applicable:

**6.1.1.1** Coating, catalyst, additive, solvent and reducer used.

**6.1.1.2** Mix ratio of components used.

**6.1.1.3** VOC content of coating as applied or solvent used in g/l or lbs/gal (less water and less exempt organic compounds).

**6.1.1.4** Material Safety Data Sheets (MSDS).

**6.1.2** Maintain records which show on a daily basis the following information:

**6.1.2.1** VOC content of the coating or solvent in g/l or lbs/gal.

**6.1.2.2** Quantity of each coating (including each specialty coating) applied and solvent used. This quantity need not include toners that are added for color matching

after preparation of the initial weighed color batch. If purchase records are used to determine the amounts of solvents used, then records and manifests of the amounts of solvents disposed of or sent to a recycler must also be maintained.

**6.1.2.3** Whether a color match was required.

**6.1.2.4** Type of vehicle (I or II) or whether mobile equipment was coated.

**6.2 Minimum Retention Time:** All records shall be retained for a minimum of two years from the date of each entry and shall be made available to DISTRICT personnel upon request.

**7 INCREMENTS OF PROGRESS:** Any person required to install any equipment in order to comply with this Rule shall submit to the APCO a complete application for an Authority to Construct permit no later than January 1, 1998, and shall complete the equipment installation required for compliance no later than July 1, 1998.

